

# MATADOR

HydroPak® MATADOR is matrix active soil surfactant

## PRODUCT DESCRIPTION

- **HydroPak® MATADOR** is a safe non-ionic wetting agent, based on innovative block polymer technology designed to establish and maintain a consistent moisture level in the root zone.
- **HydroPak® MATADOR** works by breaking down the hydrophobic coatings found in certain soil profiles reducing water repellency.
- **HydroPak® MATADOR** balances the root zone moisture conditions which: Improves oxygen levels—Increases microbial activity—Improves plant stress tolerance—Increases plant metabolism.
- **HydroPak® MATADOR** is safe to use on all types of turf throughout the growing season.

## PRIMARY FUNCTIONING AGENT

Blend of Alkyl Block Co-Polymers.....100.0%

## PRODUCT INFORMATION:

Packaging: 2 x 2.5 Gallon Case  
 Weight per Gallon: 8.5 lbs  
 pH: 7.5

## GENERAL USE GUIDE

This product can be mixed with liquid fertilizers and other surfactants. Always perform a compatibility test before tank mixing.

<b>Curative Application: Golf Course Greens, Tees, &amp; Fairways</b>	Apply 6.0 fl oz in 1 to 2 gallon of water per 1,000 sq ft. Water in with sufficient irrigation to move product well into the root zone. Follow up application should be made on 4 week intervals (see Turf Maintenance Rates below).
<b>Maintenance Rates: Golf Course Greens, Tees &amp; Fairways</b>	Apply 2.0 fl oz per 1,000 sq ft every 2 weeks or apply 4.0 fl oz per 1,000 sq ft every 4 weeks. Rates or intervals may have to be adjusted depending on soil and environmental conditions.
<b>Lawn Care Athletic Fields Sod Installation</b>	Apply 2.0 to 4.0 quarts per acre. Repeat every 4 to 8 weeks during the growing season. Rates and spray intervals will vary according to soil and environmental conditions.
<b>Sod Pre Cutting</b>	Apply 1 to 2 gallon per acre using 50 to 100 gallons of water per acre 2 to 3 weeks before cutting. Water in application with at least 1 inch of water.
<b>Spreader/Activator</b>	Apply 2.0 to 4.0 fl oz per 100 gallons of spray mixture. In difficult wetting situations such as hard water, the addition of a pH reducing agent is recommended.

*NOTICE: ENP Investments LLC warrants that the product conforms to its chemical description and is reasonably fit for the purposes stated on the label when used in accordance with the directions under normal conditions of use. ENP Investments LLC will not be responsible for incidental or consequential damage resulting from the use of this product contrary to instructions or under abnormal conditions or under conditions not reasonably foreseeable to ENP Investments LLC.*